



## LED DIALS

Clearly visible dial position indicators make operating easy.

## TOUCH CONTROL

The input selection and power on/off buttons are sleek touch buttons. Fewer moving parts means less noise and more reliable.



## 4 STEREO INPUTS

Plenty of line-level inputs to suit a range of applications.

## STEREO OUTPUT

A line-level output means it can supply a larger external amplifier if the internal amplifier is too small for some applications (e.g. school hall). Or it could feed a sub-woofer, or recording equipment.

## PHANTOM POWER MIC INPUT

Soundfield-enabled XLR microphone input to support any kind of professional microphone, including condenser or wireless mics.

## DIGITAL

2 x 25w RMS @ 8 Ohms allows compact half-rack chassis and zero power usage when idle.

## CEILING AMP

Mains-power output allows the amp and a projector to share a single power point in the ceiling. Route the audio through the projector to the amp which is hidden in the ceiling. Secure, discreet, and you can use the projector remote to adjust volume.

## GROUND LIFT

As a professional amplifier if there are any earth hums caused by dirty power or ground loops in the signal path, the amp has a ground-lift switch.

## MOUNTING EARS

Included Mounting hardware allow the amp to be attached to a wall, projector pole, or rack.



Wall/Table Configuration



Ceiling Pole Configuration



Rack Configuration

## SPECIFICATIONS

**AMPLIFIER DIMENSIONS:** 220 x 148x 44mm

**CARTON DIMENSIONS:** 265 x 211 x 145mm

**AMPLIFIER WEIGHT:** 1.2kg

**PACKAGED WEIGHT:** 2.8kg

**COLOUR:** Black

### INPUTS

4 x Stereo inputs via phono connectors  
1 x Microphone inputs via balanced XLR

### OUTPUTS

1 x Stereo Line-level output via phono connectors

### TECHNICAL DETAILS

2 x 25w @ 8 ohms  
Total Harmonic Distortion <2%  
Frequency response (line in): 20Hz~17kHz  
Signal to noise ratio (line in): 75dB  
Rating input level/Impedance:  
line in 400~450mV/47kohms  
Power consumption (rating condition): <=100W

### ACCESSORIES INCLUDED

1 x 2-phono to 2-phono cable 2m long  
1 x 2-phono to 3.5mm minijack cable 2m long  
1 x Euro Figure-8 Power cable 2m long  
1 x UK Figure-8 Power cable 2m long  
2 x Unshielded Speaker Cable 5m long  
1 x Pair wall/pole mounting ears  
1 x Pair rack mounting ears

**POWER SUPPLY:** 100~240V Internal Power Supply

**PALLET QUANTITY:** 264pcs

**WARRANTY:** 2-year return to base

**COMPLIANCES:** RoHS, WEEE & CE compliant

**ORDER PART CODE:**

AV-1500 1584480

## ASK DAVE...

If you have any questions just ask Dave. He's an installer just like you and he'll be happy to help. Go to [www.visionaudiovisual.com/askdave](http://www.visionaudiovisual.com/askdave)

